



## Cryogenic RFID Witnessing System

### COMBINATION READER MK2

THE COMBINATION READER MK2 IS THE NEXT ITERATION OF THE COMBINATION READER SERIES.

This version has undergone significant design changes. It now incorporates a barcode scanner module that reads barcoded vials from a fixed position. The combination reader now uses a USB C port for the power supply and data transfer. It also incorporates the latest RFID reader module.

#### SPECIFICATIONS

|                           |  |
|---------------------------|--|
| Communication             | USB C  |
| Power Requirement         | Power via USB  |
| Dimensions L x W x H (mm) | 173.5x100x82   |
| Weight                    | 192g   |
| LED                       | Green LED indicated if unit is powered on<br>Red LED flashes when motion is detected |
| RFID                      | ISO15693 High Frequency 13.56 MHz<br>I-CODE1 and ISO/IEC 15693 protocols             |
| Data Rates                | 115.2 kbit/s   |
| Protection Rating         | IP 54  |
| Operating Temperature     | -40 to +80 °C  |
| Storage Temperature       | 0 to +35 °C  |
| Case Material             | Nylon 12   |
| Software                  | Cryogatt reader API compatible with Windows 10 and 11                                |
| Warranty                  | 1 year   |

**WANT TO FIND OUT MORE ABOUT CRYOGENIC RFID? CONTACT US.**

Specifications may change without notice. Third party trademarks acknowledged.

Si212/V1

© 2023 Planer Ltd

**PLANER**  
PRESERVE / PROTECT / NURTURE

A Hamilton Thorne Company

[www.planer.com](http://www.planer.com)

Manufactured by:  
Cryogatt Systems Ltd  
7, Abbots Business Park  
Primrose Hill, Kings Langley  
WD4 8FR, United Kingdom

Planer Limited  
110 Windmill Road  
Sunbury-On-Thames  
TW16 7HD, United Kingdom  
+44 (0)1932 755 000

Contact us: [planer.com/contact](http://planer.com/contact)